

Serial No.: 10/698,088  
Art Unit: 2853

**LISTING OF THE CLAIMS**

1-25. (Canceled)

**BEST AVAILABLE COPY**

26. (Previously Presented) A print cartridge comprising:

a cartridge body having a lower portion and a vertical wall;

a printhead coupled with the lower portion; and

a contact array comprising a plurality of contact areas disposed on the vertical wall, the contact array being one selected from a group comprising a first contact array that has a first layout of contact area locations, and a second contact array that has a second layout of contact area locations, wherein a portion of the contact area locations of the first layout and a portion of the contact area locations of the second layout are the same, and another portion of the contact area locations of the first layout and another portion of the contact area locations of the second layout are different, and wherein the another portion of the contact area locations of the first layout and the another portion of the contact area locations of the second layout are coupled to provide identification information for the print cartridge.

27. (Previously Presented) The print cartridge of claim 26, wherein the another portion of the contact area locations of the first layout and the another portion of the contact area locations of the second layout include some of the same contact area locations.

28. (Previously Presented) The print cartridge of claim 26, wherein the another portion of the contact area locations of the first layout and the another portion of the contact area locations of the second layout do not include some of the same contact area locations.

29. (Previously Presented) The print cartridge of claim 28, wherein the portion of the contact area locations of the first layout and the second layout is coupled to a component selected from the group consisting of temperature sense resistors, inactive contacts, and ground contacts.

Serial No.: 10/698,088

Art Unit: 2853

30. (Original) The print cartridge of claim 26, wherein first layout includes a first pair of columnar arrays of contact areas and a second pair of columnar arrays of contact areas disposed on the vertical wall, the columnar arrays of each pair converging toward each other in a direction toward the lower portion of the cartridge body.

31. (Original) The print cartridge of claim 26, wherein the first layout and the second layout each has a width of less than about 12 mm.

32. (Original) The print cartridge of claim 26, wherein a number of contact areas in the portion of the first layout and the second layout are a same in number.

33-34. (Canceled)

**BEST AVAILABLE COPY**